



58, Paige Close, The Meadows, Watlington
 King's Lynn, Norfolk PE33 0TQ
 Tel 01553 811977 Fax 01553 811004 Mobile 07768506297
 E-mail: sales@manualhandlingsolutions.co.uk
www.manualhandlingsolutions.com

MezzLift Specification – 250kg for DRS Bracknell

Maximum Working Load	250kg
Travel	3240mm floor to floor
Platform Size	1000mm x 1000mm to suit application
Platform Guarding	900mm high frames to two sides to suit loading direction
Lift Speed	0.3 m/s
Number of stops	2 (ground and mezzanine)
Power Supply Required	240v, 20amp, 1 phase terminated in a double pole isolator switch
Controls	Push to run controls adjacent to the gates at both levels
Drive Type	Chain drive, hydraulic motor
Loading Configuration	Load Through
Pit	None – loading via 50mm ramp
External Shaft Size	1610mm x 1210mm
Shaft Enclosure	Self supporting 1" x 1" mesh shaft
Door Type	2000mm Clear height double gate at lower level and single gate at upper level, mesh filled. Gates are protected by electrical interlocks to prevent access to the shaft unless the platform is docked at the appropriate level
Documentation	CE Mark with Declaration of Conformity Operation and Maintenance Manual issue on completion
Training	LOLER Report of Thorough Examination and Test issued on commission Operator training carried out on completion

